MTV-73S10H COLOR CAMERA INSTRUCTION

Caution for Installation


- 1. Avoid places where there is direct sunlight. When using the camera outside.
- 2. Be careful, never let any water in this equipment.
- 3. Do not directly touch the CCD element. If necessary, use a soft cloth moistened with alcohol to wipe off the dust.
- 4. When the camera installs in dust or wet environment, please puts into the camera housing.
- 5. Be extra careful not to shake the camera.
- 6. Avoid places where temperatures exceed 50°C or more.
- 7. When any abnormalities occur, make sure to unplug the unit and contact your local dealer.
- 8. The camera are only operated with regulative adaptor DC 12V,
- AC to DC non-regulative adaptor may cause camera damaged.

SPECIFICATION (RoHS Conform)

MODE NO.		MTV-73S10HN	MTV-73S10HP	
TV SYSTEM		NTSC	PAL	
IMAGE SENSOR		1/3-inch I.L. CCD Image Sensor		
CCD TOTAL PIXELS		~ 410K	~ 470K	
SYNC SYSTEM		Internal		
MINIMUM ILLUMINATION		> 0.012 lux@F1.2 /20 IRE AGC on B/W > 0.0014 lux@F1.2 /20 IRE SENS-UP (32X) B/W		
LENS & VIEW ANGLE				
RESOLUTION		540TVL		
WHITE BALANCE	Mode	ATW / AWC		
WITTE DALANCE	Range		3200 ~ 10000 °K	
S/N RATIO		50dB (MIN) / 58dB (TYP) (Gamma, Aperture, AGC, OFF)	
DNR (Digital Noise Reduce)		S/N UP 4.5dB		
GAIN CONTROL		AGC ON / OFF		
SENSE UP		ON /OFF (Preset X4 ,Option X32)		
H - MIRROR FUNCTION		OFF / ON		
V - MIRROR FUNCTION		OFF / ON		
B.L.C. FUNCTION		ON / OFF		
COLOR BAR		OFF / ON		
AUTO IRIS		A.E.S. / DC-IRIS		
ELECTRONIC SHUTTER		1/60~1/120,000 sec.	1/50~1/120,000 sec.	
VIDEO OUTPUT		1.0V p-p composite video at 75 ohm With monitor output		
OPERATION TEMPERATURE		-20°C to 50°C		
OPERATIONAL HUMIDITY		within 85% RH		
POWER SUPPLY		DC12V±1V / 150mA		


^{*} The specifications and appearance of the product may changed without notice.

Dimension: Unit (mm $/\pm 0.5$ mm)



Auto IRIS

Lens Connector:



DC-LENS			
P1	DUMP-		
P2	DUMP+		
P3	DRIVE		
P4	GND		

Function Switch

FUNCTION SWITCH		1	0				
S1	AES/ALC	AES	ALC				
S2	AGC	AGC ON	AGC OFF				
S3	ATW/AWC	ATW	AWC				
S4	BLC	BLC ON	BLC OFF				
S5	H-MIRROR	NORMAL	MIRROR				
S6	V-MIRROR	NORMAL	MIRROR				
S7	SENS-UP (X4)	SENS-UP ON	SENS-UP OFF				
S8	VIDEO/COLOR BAR	VIDEO	COLOR BAR				