

# WAT-2400S

1/2.8" Compact High Sensitivity Network Color Camera


As small as WAT-902 series



## Key features

- Supporting microSD enables stand-alone recording without the network connection
- Video output quick start-up in 6 sec.
- Power-saving PoE : 2.40W/50mA DC+12V : 1.80W/150mA

## Dimensions



## Specifications

Pick-up element	1/2.8 inch BSI CMOS image sensor	
Number of effective pixels	1945(H) × 1097(V)	
Unit cell size	2.9µm(H) × 2.9µm(V)	
Imaging system	RGB primary color bayer arrangement mosaic filter on chip	
Synchronizing system	Internal	
Scanning system	Progressive	
Output size	1920×1080, 1280×720, 800×600, 704×480, 704×400, 640×480, 640×360, 320×240	
Max. frame rate	60 fps	
Video compression	H.264, MJPEG	
Minimum illumination	0.007 lx F1.2 (AGC HIGH=72dB, Shutter=OFF)	
S/N	-	
Function settings	Browser	
AE mode	Fixed	1/30, 1/60, 1/120, 1/250, 1/500, 1/1000, 1/25, 1/50, 1/100, 1/200, 1/400, 1/800, 1/2000, 1/4000, 1/8000, 1/15000, 1/1600, 1/3200, 1/6400, 1/12800,
		1/30000 (sec.) *1 1/25600 (sec.) *2
	EI	1/30 - 1/30000 (sec.) *1 1/25 - 1/25600 (sec.) *2
		×32 - 1/30000 (sec.) *1 *3 ×32 - 1/25600 (sec.) *2 *3
White balance	ATW, PWB, MWB, PRESET (3000K, 5000K, 8000K)	
AGC	ON	0 - 72dB
	OFF	0dB
MGC	-	
Day/Night	-	
Noise reduction	3DNR OFF/ON (Level adjustable)	
Wide dynamic range	WDR OFF/ON (Level adjustable)	
Lens iris	DC	
Back light compensation	BLC, HSBLC	
White blemish correction	ON	
Sharpness	Level adjustable	
Defog	OFF/ON (Level adjustable)	
Digital zoom	-	
Privacy mask	16 masks	
Mirror image	OFF, V-FLIP, H-FLIP, HV-FLIP	
Freeze	-	
Motion detection	OFF/ON 4 areas arbitrarily configurable	
Neg.image	-	
ONVIF	profile S	
Supported protocols	TCP/IP, UDP/IP, RTP(RTCP), RTSP,	
	SNTP, HTTP, FTP, DHCP, DNS	
Interface	RJ45 (10BASE-T, 100BASE-TX), 4P Connector (MIC. IN, POWER IN), Auto iris, microSD (Recommended: SDHC / SDXC standard, MLC type, Speed Class CLASS 10 or more, Capacity of 256GB or less)	
Power supply	PoE +48V (IEEE802.3af), DC+12 - 36V *+12V is recommended for DC input	
Power consumption	2.40W/50mA (PoE +48V), 1.80W/150mA (DC+12V)	
Operating temperature	0 - +50°C	
Storage temperature	-30 - +70°C	
Operating / Storage humidity	95% RH or less (Without condensation)	
Lens mount	CS mount (Back focus adjustable)	
Weight	Approx. 80g	
Accessories	4P cable, Hex. wrench, Clamp filter	

\*1: Frequency=60Hz \*2: Frequency=50Hz \*3: When using the Slow Shutter

\*ONVIF is a trademark of Onvif, Inc. \*microSD is a trademark of SD Association. SD, SDHC and SDXC (and logos) are trademarks of SD-3C, LLC.

\*XProtect is a registered trademark of Milestone Systems A/S.

Accessories Options

**CS-mount lenses**  
 \*see www.variovision.tv for more lens options

M13VG288IR M13VG850IR  
 AG3Z2812FCS-MPWIR AG4Z1214FCS-MPIR  
 \*2246H


**Miniature lenses / Mount adaptors**

M2520BC-12 M2920BC-12  
 \*401304 \*401305  
 M3620BC-12 M0620BC-12  
 \*401306 \*401302  
 28MMA-M12-155  
 \*401556  
 M0816BC-12 M1625BC-12  
 \*401303 \*503136

**C-mount lenses**  
 \*see www.variovision.tv for options

30CMA-R  
 \*402806

**WAT-2400S**



**Stands**

MS50 WH-11  
 \*402599 \*303041  
 WH-21 WH-31  
 \*303042 \*303040

**Water resistant camera housing / Mounting brackets**

VCHO-15S  
 WH-6N PTP-300

\*see www.variovision.tv for more options

